

## COASTLINE

Packaging, Inc.

30470 Energy Drive

New Church, VA 23415

757-824-3831

www.prideantifreeze.com

### APPLICATION GUIDE

- CAT DEAC, ELC, EC-1
- CUMMINS 90T8-4, CES14603
- DETROIT DSL 7SE298 DDC, POWERCOOL DDC, POWER-COOL3000, POWER-COOL PLUS DDC, POWERCOOL PLUS 6000
- FORD NEW HOLLAND WSN M97D18D, ESE M97B18C, M97B44A, WSE M97B44B, WSS M97B51A1, WSS M97B44D, WSN M97B18D
- FREIGHTLINER 48-2288-0
- JI CASE JIC501, MS1710
- DEERE JDM M24A1, M24B1, M24C1, H-5
- MACK 014 G517994
- MIL 0-A-5480
- MTU MTL5048, MTL5049
- NAVISTAR B1 TYPE I, II, III
- TMC RP302-A, RP329, RP338
- VOLVO ES 1709

### OTHER SPECIFICATIONS

**ASTM** D3306, D4985, D6210, D1384, D4340, D2570, D2809

**MADE IN USA**

# Pride COMMANDER 84

**HEAVY-DUTY, PRECHARGED, EXTREME LIFE ANTIFREZE/COOLANT FOR TRUCKS AND OFF-ROAD EQUIPMENT FULL STRENGTH CONCENTRATE**

PRODUCT BULLETIN

APRIL 2010

## PRODUCT DESCRIPTION

**PRIDE COMMANDER 84 is a concentrated antifreeze/coolant for heavy-duty diesel engine applications. It is formulated to blend with water for customized freeze and boil over protection. It is fully compatible with all major brands of premium anti-freeze/coolants and DOES NOT contain recycled antifreeze.**

**PRIDE COMMANDER is fully formulated or pre-charged for extreme service. NO SCA is required at fill.**

**PRIDE COMMANDER is an advanced complex of organic, carboxylate inhibitors supported with proven, fast-acting inorganic compounds.**

**PRIDE COMMANDER protects all cooling system components with multi-metal corrosion inhibitors, and has anti-scaling and lubricating properties.**

**PRIDE COMMANDER can provide protection for up to 600,000 miles with periodic FORTIFIER charge.**



**Follow engine manufacturers, recommended service intervals.**

**REMEMBER RECYCLE**

## COOLING SYSTEM RECOMMENDATIONS

A clean cooling system protects your vehicle/equipment investment. When changing coolant, always drain and flush your system thoroughly before refilling with recommended coolant.

Maintain proper coolant levels. Always top-off with premix coolant. Change coolant regularly to remove contamination that may develop from engine gases or other fluids.

## SPECIFICATIONS

<b>EG CONTENT</b>	93-95%
<b>INHIBITORS</b>	< 4 %
<b>COLOUR</b>	RED
<b>SPEC GRAVITY</b>	1.13
<b>pH</b> (as is)	8.5-9.5
<b>SILICATE</b>	nil
<b>FREEZE PT</b> (50%)	-34F
<b>BOIL PT</b> (50%)	+265F
<b>NITRITE</b>	>2200ppm