


Pride[™] XL-100



Antifreeze & Coolant

-84°F

**5 Years or 150,000 miles
You're Protected!**

PRIDE XL-100 Extended Life Antifreeze is a fully compatible, high performance antifreeze containing advanced corrosion inhibitors and stabilizers that provides long-term protection for complete cooling system protection.

- **Maximum Long Term Protection**
- **Fully Compatible with All Other Brands**
- **Protects All Metals Including Aluminum**

From the most frigid winter weather to the hottest days of summer, PRIDE XL-100 EXTENDED LIFE Antifreeze and Coolant provides maximum long-term protection. It meets or exceeds domestic and imported engine requirements for both gasoline and diesel engines and is perfect for cars or light trucks.

PRIDE XL-100 is a silicate, phosphate and nitrate free formula with foam suppressor provides helps lubricate vital cooling system components and minimizes hot surface scaling. It meets the requirements requirements for ASTM D 3306 for automotive service and ASTM D 4985 and D6210 for heavy duty diesel service.
Available in gallons and drums.

Coastline Packaging Company • 30470 Energy Drive • New Church, VA 23415

PRIDE XL-100 EXTENDED LIFE ANTIFREEZE & SUMMER COOLANT

PRIDE XL-100 Extended Life Antifreeze and Coolant is formulated in accordance with:

ASTM D3306
ASTM D4985
ASTM D6210
ASTM D1384
ASTM D4340
ASTM D2570
ASTM D2809

- American Motors AM-4085
- Audi
- BMW Mercedes Blatt 325.0, 325.2
- Caterpillar Cat DEAC, EC-1, ELC
- Chrysler MS7170, MS9769
- Cummins 90T8-4, CES14603
- Detroit Diesel 7SE298; DDC Powercool, DDC Powercool 3000, 7SE298 DDC Powercool Plus, DDC Powercool Plus 6000
- Ford New Holland WSN-M97D18D, Ford ESE M97B18-C, ESE M97B44-A, WSE M97B44-B, WSS-M97B51-A1, WSS M97B44-D, WSN M97B18-D
- Freightliner 48-22880
- GM 6038M, 1825M, 1899M, 6277M
- GSA A-A-870A, GSA A-A-52624
- Honda HES D2009-75
- Hyundai
- Isuzu
- J.I. Case JIC-501, MS1710
- John Deere JDM H24A1 H24B1, H24C1 and H5
- Mack Truck 014 GS17004
- Mazda MEZ MW 121D
- MIL O-A-5480
- Mitsubishi
- MTU MTL5048, MTL5049
- Navistar B1, Type 1, II, III
- Porsche TL-774C, TL-774D
- Saab 6901 599
- SAE J814, J1941, J1034
- Suzuki 0F02
- TMC of ATA RP302A, RP329, RP338
- Toyota TSK26016
- Volvo 014 GS 17009
- VW TL774C (G11), VW TL774D (G12), red, VW TL774F (G12), light violet

(UNIVERSAL SILICATE FREE FORMULATION)

PRODUCT SPECIFICATION

TYPICAL COMPOSITION	TYPICAL ANALYSIS
ETHYLENE GLYCOL (ANTIFREEZE GRADE)	94.4% min.
CORROSION INHIBITORS	2.1%
WATER	5% max.
ANTIFOAM & RED DYE	Trace
TYPICAL PROPERTIES	
COLOR	Fluorescent Orange-Red
SPECIFIC GRAVITY @ (60 F)	1.12 - 1.13
RESERVE ALKALINITY	3.0 min.
pH, 50% BY VOLUME	8.5 - 10.0
FLASH POINT, (Tag Open Cup)	250F
BOILING POINT	276F min.
FOAM TEST	50ml. / 3sec. max.
FREEZE POINT @ 50%	-34F
SILICATE	nil
POUNDS PER GALLON	9.4

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

PRIDE XL-100 Permanent Extended Life Antifreeze and Coolant is an ethylene glycol based universal formulation with HOAP additive, which performs equally well in aluminum and conventional metal engines. Recommended for passenger cars, trucks, tractors, heavy-duty commercial engines and stationary engines. Compatible with all nationally distributed antifreeze brands and supplemental coolant additives. Fully formulated and precharged for diesel engine applications. SCA's not required at initial fill. Add ESA/SCA's at recommended service intervals. PRIDE XL-100 Permanent Extended Life Antifreeze and Coolant does not adversely affect automotive hoses, gaskets or paint finishes.

HANDLING AND SAFETY INFORMATION

Refer to PRIDE XL-100 Material Safety Data Sheet (MSDS) for proper handling and safety information.

DISTRIBUTED BY:



Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

**Also available in Quarts and Bulk upon request.*

Keep America Beautiful - Don't Pollute
Return Used Fluid To Collection Center